

Model		Display /Size	Keys / LED's	Digital Inputs	Digital Outputs	Analogue Inputs	Analogue Outputs	Serial Ports	Ethernet	USB + Compact Flash
HI 125P		128 * 64(1.25") LCD-Monochrome 48x48x76mm	8/0	8	8	--	--	2	--	--
HI 126P		128 * 64(1.25") LCD-Monochrome 48x48x76mm	8/0	6	6	1 (Univ.) 12bit	1 (4-20mA) 12bit	2	--	--
HI 300P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	12	--	--	2	--	--
HI 301P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	2 PWM 10 relays 2A@230V	--	--	2	--	--
HI 302P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	12	4 (Univ.) 12bit	2 (4-20mA) 12bit	2	--	--
HI 303P		128 * 64 (3") LCD-Monochrome 183x101x37mm	18/4	16	2 PWM 10 relays 2A@230V	4 (Univ.) 12bit	2 (4-20mA) 12bit	2	--	--
HI 410P		192 * 64 (4") LCD-Monochrome 140x77x35mm	Touch screen	16	12	--	--	2	--	--
HI 411P		192 * 64 (4") LCD-Monochrome 140x77x35mm	Touch screen	12	8	4 (mA)10bit 2 (Univ)12bit	1 (4-20mA) (0-10V)	2	--	--
HI 412P		192 * 64 (4") LCD-Monochrome 140x77x35mm	Touch screen	16	12	2 (Univ.) 12bit	--	2	--	--
HI 570		320 *240(5.7") STN-16 grey scales 197x139x52mm	Touch screen	--	--	--	--	2	--	--
HI 572RP		320 *240(5.7") STN-16 grey scales 197x139x52mm	Touch screen	28	2 PWM 14 relays 2A@230V	--	--	2	--	--
HI 573RP		320 *240(5.7") STN-16 grey scales 197x139x52mm	Touch screen	28	2 PWM 14 relays 2A@230V	4 (Univ.) 12bit	2 (4-20mA) (0-10V)	2	--	--
HI 575		320 *240 (5.7") STN color 197x139x52mm	Touch screen	--	--	--	--	2	--	--
HI 576		320 *240 (5.7") STN color 197x139x52mm	Touch screen	--	--	--	--	2	1	--
HI 577P		320 *240 (5.7") STN color 197x139x52mm	Touch screen	28	16	4 (Univ.) 12bit	2 (4-20mA) (0-10V)	2	--	--
HI 577RP		320 *240 (5.7") STN color 197x139x52mm	Touch screen	28	2 PWM 14 relays 2A@230V	4 (Univ.) 12bit	2 (4-20mA) (0-10V)	2	--	--
HI 578RP		320 *240 (5.7") STN color 197x139x52mm	Touch screen	28	2 PWM 14 relays 2A@230V	--	--	2	--	--
HI 1200		800 *600(12.1") TFT-Color 312x246x44mm	Touch screen	--	--	--	--	2	--	--
HI 1202		800 *600(12.1") TFT-Color 312x246x44mm	Touch screen	--	--	--	--	2	1	1

INPUTS/OUTPUTS MODULES (DIN Rail)

Model	Dimensions 70x100x35mm	Digital Inputs	Digital Outputs	Analogue Inputs	Analogue Outputs	Serial Ports
HI 42A		--	--	4 (Univ.) 12bit Pt-100, TC 0/4-20mA 0-10V 0-50/100mV	2 (V, mA) 12bit 0-10V 4-20mA	1
HI 80AL		--	--	8 (V,mA) 12bit 0-10V 4-20mA	--	1
HI 0808R		8	8 relays 2A@230VAC	--	--	1

ACCESSORIES

14000242	Compact Flash Memory 256Mb
14000243	USB Adapter <-> RS232C (DB9)
19500021	Programming cable RS232 from PC (DB9) <-> HIMOS (DB9)
19500022	Programming cable RS232 from PC (DB9) <-> HIMOS (RJ45)
19500023	Connection Cable RS2 KOSMOS (RJ11) <-> HIMOS (DB9)
19500024	Connection Cable RS4 KOSMOS (RJ12) <-> HIMOS (DB9)
19500025	Connection Cable RS2 KOSMOS (RJ11) <-> HIMOS (RJ45)
19500026	Connection Cable RS4 KOSMOS (RJ12) <-> HIMOS (RJ45)
19500027	Connection Cable PLC SIEMENS S7-MICRO <-> HIMOS (DB9)
19500028	Connection Cable PLC SIEMENS S7-MICRO <-> HIMOS (RJ45)
19500029	Connection Cable PLC OMRON CQM (DB9) <-> HIMOS (DB9)
19500030	Connection Cable PLC OMRON CQM (DB9) <-> HIMOS (RJ45)
19500031	Connection Cable PLC TELEMECANIQUE (TSX07/37)/HIMOS(DB9)
19500032	Connection Cable PLC TELEMECANIQUE (TSX07/37)/HIMOS(RJ45)

SOFTWARE

HIMOSOFT	free programming software available on http://www.ditel.es
-----------------	--